

# GUI Components: Part 2, Solutions

# 25

*An actor entering through the door, you've got nothing. But if he enters through the window, you've got a situation.*

—Billy Wilder

*...the force of events wakes slumberous talents.*

—Edward Hoagland

*You and I would see more interesting photography if they would stop worrying, and instead, apply horse-sense to the problem of recording the look and feel of their own era.*

—Jessie Tarbox Beals

## Objectives

In this chapter you'll learn:

- To create and manipulate sliders, menus, pop-up menus and windows.
- To programmatically change the look-and-feel of a GUI, using Swing's pluggable look-and-feel.
- To create a multiple-document interface with `JDesktopPane` and `JInternalFrame`.
- To use additional layout managers.

## Self-Review Exercises

**25.1** Fill in the blanks in each of the following statements:

a) The \_\_\_\_\_ class is used to create a menu object.

ANS: JMenu.

b) The \_\_\_\_\_ method of class JMenu places a separator bar in a menu.

ANS: addSeparator.

c) JSlider events are handled by the \_\_\_\_\_ method of interface \_\_\_\_\_.

ANS: stateChanged, ChangeListener.

d) The GridBagConstraints instance variable \_\_\_\_\_ is set to CENTER by default.

ANS: anchor.

**25.2** State whether each of the following is *true* or *false*. If *false*, explain why.

a) When the programmer creates a JFrame, a minimum of one menu must be created and added to the JFrame.

ANS: False. A JFrame does not require any menus.

b) The variable fill belongs to the GridBagConstraints class.

ANS: False. The variable fill belongs to the GridBagConstraints class.

c) Drawing on a GUI component is performed with respect to the (0, 0) upper-left corner coordinate of the component.

ANS: True.

d) The default layout for a Box is BorderLayout.

ANS: True.

**25.3** Find the error(s) in each of the following and explain how to correct the error(s).

a) JMenuBar b;

ANS: JMenuBar should be JMenuBar.

b) mySlider = JSlider( 1000, 222, 100, 450 );

ANS: The first argument to the constructor should be either SwingConstants.HORIZONTAL or SwingConstants.VERTICAL, and the keyword new must be used after the = operator. Also, the minimum value should be less than the maximum and the initial value should be in range.

c) gbc.fill = GridBagConstraints.NORTHWEST; // set fill

ANS: The constant should be either BOTH, HORIZONTAL, VERTICAL or NONE.

d) // override to paint on a customized Swing component  
public void paintcomponent( Graphics g )  
{

    g.drawString( "HELLO", 50, 50 );

} // end method paintComponent

ANS: paintcomponent should be paintComponent, and the method should call super.paintComponent( g ) as its first statement.

e) // create a JFrame and display it

JFrame f = new JFrame( "A Window" );

f.setVisible( true );

ANS: The JFrame's setSize method must also be called to establish the size of the window.

## Exercises

*NOTE: Solutions to the programming exercises are located in the ch25solutions folder. Each exercise has its own folder named ex25\_## where ## is a two-digit number representing the exercise number. For example, exercise 25.14's solution is located in the folder ex25\_14.*

- 25.4** Fill in the blanks in each of the following statements:
- A `JMenuItem` that is a `JMenu` is called a(n) \_\_\_\_\_.  
ANS: submenu.
  - Method \_\_\_\_\_ attaches a `JMenuBar` to a `JFrame`.  
ANS: `setJMenuBar`.
  - Container class \_\_\_\_\_ has a default `BoxLayout`.  
ANS: `Box`.
  - A(n) \_\_\_\_\_ manages a set of child windows declared with class `JInternalFrame`.  
ANS: `JDesktopPane`.
- 25.5** State whether each of the following is *true* or *false*. If *false*, explain why.
- Menus require a `JMenuBar` object so they can be attached to a `JFrame`.  
ANS: True.
  - `BoxLayout` is the default layout manager for a `JFrame`.  
ANS: False. `BorderLayout` is the default layout manager for `JFrame`.
  - `JApplets` can contain menus.  
ANS: True.
- 25.6** Find the error(s) in each of the following. Explain how to correct the error(s).
- `x.add( new JMenuItem( "Submenu Color" ) ); // create submenu`  
ANS: A `JMenu` is used to create a submenu, not a `JMenuItem`.
  - `container.setLayout( new GridbagLayout() );`  
ANS: `GridbagLayout` should be `GridBagLayout`.
- 25.9** Explore the effects of varying the `weightx` and `weighty` values of the program in Fig 25.21. What happens when a slot has a nonzero weight but is not allowed to fill the whole area (i.e., the `fill` value is not BOTH)?
- ANS: When the weight is non-zero but the component is not allowed to fill in both directions, blank space is created around the component. The amount of space allocated for the component in the panel is the same as if it could expand to fill the space, but the component does not stretch in that direction.

